

# rotherm spiral needed

<b>Style No.</b>	2951
<b>Color</b>	white
<b>Weight</b>	1,63 kg/m <sup>2</sup> / 0.33 lbs/ft <sup>2</sup> 1,78 kg/m <sup>2</sup> / 0.36 lbs/ft <sup>2</sup>
<b>Overall gauge</b>	0.2 in 5 mm
<b>Tensile strength</b>	34 lbs/in 72 N/mm
<b>Recommended working tension</b>	11 – 28 lbs/in 2 – 5 N/mm
<b>Minimum pulley diameter</b>	2 in 50 mm
<b>Temperature range</b>	–22 to +428 °F –30 to +220 °C
<b>Compound (by your choice)</b>	PET/Nomex PET/PE PET/PA
<b>cfm</b>	80 – 180

#### Advantages:

- with fleece layers
- hydrolysis resistant
- with seam or seamless
- no marking

#### Product Availability:

Available widths: 100 – 8000 mm / 4" – 26.2'

Available length: 5 – 100 m / 16.4' – 325'



### Felts and Dryer Fabrics

for the Paper Industry

### Filter Screens and Conveyor Belts

for Manufacturing Plants

Filtzuchfabrik Rodewisch GmbH  
Polenzstrasse 101  
D-08485 Lengenfeld, Germany  
Tel.: +49 (0) 376 06-3 80  
Fax: +49 (0) 376 06-3 81 10  
Email: post@filtzuch.de  
Internet: www.filtzuch.de

**Rodewisch**  
ATTENTION TO DETAIL

