

Aquaflow Felt

Style No.	3323 – 3824
Color	white
Weight	1,00 – 1,60 kg/m ² 0,25 – 0,40 lbs/ft ²
Overall gauge	0.08 – 0.16 in 2 – 4 mm
Tensile strength	257 lbs/in 45 N/mm
Recommended working tension	11 – 22 lbs/in 2 – 4 N/mm
Minimum pulley diameter	4 in 100 mm
Temperature range	up to 197 °F up to 100 °C
Compound	Polyamide
Plies	two-woven
Chemically resistant	pH 6 – 13
cfm	50 – 200

Advantages:

- easy cleaning
- fast start up
- very stable in CD
- maximum working stretch = 1 %
- smooth running at all speeds
- high dewatering
- long lifetime

Product Availability:

Available widths: 100 – 8000 mm / 4" – 26.2'

Available length: 8 – 27 m / 26.2' – 88.4'



Felts and Dryer Fabrics

for the Paper Industry

Filter Screens and Conveyor Belts

for Manufacturing Plants

Filztuchfabrik Rodewisch GmbH
 Polenzstrasse 101
 08485 Lengenfeld, Germany
 Tel.: +49 (0) 376 06-3 80
 Fax: +49 (0) 376 06-3 81 10
 Email: post@filztuch.de
 Internet: www.filztuch.de

Rodewisch
 ATTENTION TO DETAIL

